

EURO-SEEDING® HYDROSEEDER FINN® T 90 S / 120 S

EQUIPMENT

Hydroseeder



TECHNICAL SPECIFICATIONS

- ▶ Tank size: T90 S: 3,560 liters T120 S: 4,460 liters
- ▶ Power: Kubota Diesel, 33.5 HP, liquid cooling
- ▶ Pump: Centrifugal – 10 cm x 5 cm – 646 lpm @ 100 psi
- ▶ Mixing: Mechanical and hydraulic agitation
- ▶ Discharge distance: 55 meters (from the discharge gun)
- ▶ Tank emptying time: 6 minutes
- ▶ Maximum product load:
 - Solid pellets / fertilizer T90 S: 1,160 kg T120 S: 1,450 kg
 - Fibers (mulch) T90 S: 180 kg T120 S: 225 kg
- ▶ Empty weight / working weight: T90 S: 1,814 kg / 6,010 kg
T120 S: 2,032 kg / 7,294 kg
- ▶ Dimensions (W x L x H): T90 S: 203 cm x 335 cm x 125 cm (top of tank)
and 257 cm (boom clearance)
T120 S: 203 cm x 391 cm x 125 cm (top of tank)
and 257 cm (boom clearance)
- ▶ Options available: Hydraulic hose reel with a 60-m hose



L'OFFRE EURO-TEC



HYDROSEEDING HYDROSEEDER
EUROTEC GREEN ROOF
BARK BLOWER HYDROSEEDING
SOIL GUARD JUTE GEOTEXTILE
COCO GEOTEXTILE VERTOIT
HYDROSEEDING EURO-FEUTRE
EURO-MAT COCO LOGS
EURO-SEEDING
HYDROSEEDING CONSUMABLES
EURO-TEC EURO-TEXTILE
HYDRO-MULCH KRISMER

